

Actinide Target Station & ^{238}U Photofission Yield

Pierre Bricault
SEEC, 25-26 March 2008



CANADA'S NATIONAL LABORATORY FOR
PARTICLE AND NUCLEAR PHYSICS
LABORATOIRE NATIONAL CANADIEN
POUR LA RECHERCHE EN PHYSIQUE NUCLÉAIRE
ET EN PHYSIQUE DES PARTICULES




Conseil national
de recherches Canada

National Research
Council Canada

Canada



TRIUMF Layout




- Next 5-YP
- Three RIB to users
 - One RIB from actual ISAC
 - Proton Beam line ($< 200 \mu\text{A}$; 475 MeV)
 - Electron Beam producing photofission (10 mA ; 50 MeV)

- **More RIB to USers**
- **New Target Station Compatible with Actinide Target Material**
- **New High Intensity Beam Dump: at least 200 μ A**
- **We are proposing a solution to deliver Three RIB to Users**
 - **One RIB from actual ISAC**
 - **Proton Beam line (< 200 μ A; 475 MeV)**
 - **Electron Beam producing photofission (10 mA ; 50 MeV)**
- **First of all, new target stations has to be compatible with actinide target.**


- The target station is an assembly of 5 modules, entrance, target and beam dump, plus two exit modules containing the heavy ion optics elements for beam preparation to the mass separator.

Advantages of the ISAC target station concept


1. The modular approach permits use of high intensity (up to $100\ \mu\text{A}$) proton beam on target.
2. Non-hard radiation material are located in a zone where the radiation fields are low enough.
3. Front end optics can be exchanged as well as the target.



- **Disadvantages of the ISAC target station concept**
 1. Actual confinement box housing the target is not hermetic.
 2. Hand on connection and disconnection of the target services.
 3. The target can not be conditioned and ready for use,
 4. Target module has to move from the target station to the hot-cell, ~ 30 m.
 5. Air sensitive material such as LaC and UC creates extra difficulties.
 6. Target exchange takes from 3 to 5 weeks, or requires proton beam off periods for installation.



Target module



Other Findings


- **In the present situation we have the possibility to deliver only one RIB at the time for physics.**
- **Our two target stations are sharing the same mass separator.**
- **Maintenance in the target hall is using approximately 25-30% of the time.**
- **RIB development is also taking 25% of the time.**
- **These effects reduce beam time for experiments.**
- **Need more beams deliver to ISAC users.**

Solutions

- **Target has to be inside a completely sealed containment box,**
 - **Handling,**
 - **conditioning before use,**
- **Target/ion source services has to be connected remotely,**
- **One Hot-cells dedicated to target/ion source exchange only,**
- **Two target stations has to work completely independently of each other,**
 - **Independent mass separator,**
 - **Independent cooling water,**
 - **Independent nuclear ventilation,**
- **We must be able to service one target station while the other one is delivering RIB to experiment or beam R&D.**




Target exchange



- To exchange the target it takes from 3 (need two shifts without proton beam) to 5 weeks,
- Its forces us to run our target much longer than we should,
- Low yield because of the radiation damage.



Target exchange



- We are proposing to exchange the target within two days,
- We will have a dedicated hot-cell to exchange the target. The new target will be conditioned and ready for on-line operation before it is installed in the target station.

Photofission

- Photofission of ^{238}U has been proposed in 1999 by W. T. Diamond [NIM, v 432, (1999)p471] as an alternative to produce RIB in Chalk River.
- The idea was later push a little further by Y. T. Oganessian in 2000 [RNB2000, Nucl. Phys. A 701 (2002) p 87],
- The continuous gamma spectrum produce by electron is utilized to excite the giant dipole resonance (GDR) in ^{238}U .




Basic Parameters


Item	Value	Units
Electron energy	50	MeV
Total power	0,5	MW
Electron current	0,01	Ampère
Target, UC ₂	15	g/cm ²

- Assuming same target/ion source design in use at ISAC

Low electron beam power < 25 kW




High electron beam power > 25 kW





ISAC Target/Ion Source

$P < 5 \text{ kW}$

Target container
20 mm diameter
20 cm long







$P \sim 10 \text{ kW}$



ISAC Target/Ion Source

- Cooling concept for $P \sim 20 - 30 \text{ kW}$





Electron Energy & Radiation

$$\frac{dE_{Rad}}{\rho dx} \simeq -\frac{E}{X_0}$$

$$\frac{1}{X_0} = \frac{4\alpha N_A Z(Z+1)r_e^2 \log(183Z^{-1/3})}{A}$$

$$\overline{E} \simeq E_0 \exp\left(-\frac{\rho \Delta x}{X_0}\right)$$

- **E** is the electron energy
- **$\alpha \sim 1/137$**
- **N_A is the Avogadro number, 6,023e23 at/mole**
- **Z is the material atomic number**
- **r_e is the classical electron radius $\sim 2,818\text{e-}13$ cm**
- **A is the molar mass of the material**

Element	Z	A	ρ (g/cm ³)	1/ X_0	X_0 (g/cm ²)	τ (cm)
Al	13	27	2,3	0,0178	56,17	24,42
Cu	29	63,5	8,92	0,0340	29,45	3,30
Ta	73	181	16,65	0,0684	14,62	0,88
W	74	184	19,25	0,0691	14,48	0,75
Hg	80	202	13,58	0,0729	13,71	1,01
Pb	82	208	11,34	0,0742	13,47	1,19


Photon Distribution

- Using the Born approximation, Bethe, Heitler, Sauter and Racah developed an expression that gives the photo energy distribution


$$d\sigma_k = 2\alpha Z^2 r_0^2 \frac{dk}{k} \left[\left(1 + \left(\frac{E}{E_0} \right)^2 - \frac{2}{3} \frac{E}{E_0} \right) \left(\ln M(0) + 1 - \frac{2}{b} \tan^{-1} b \right) + \frac{E}{E_0} \left[\frac{2}{b^2} \ln(1 + b^2) + \frac{4(2 - b^2)}{3b^2} \tan^{-1} b - \frac{8}{3b^2} + \frac{2}{9} \right] \right]$$

$$b = \left(\frac{2E_0 E Z^{1/3}}{111 k} \right) \quad \frac{1}{M(0)} = \left(\frac{k}{2E_0 E} \right)^2 + \left(\frac{Z^{1/3}}{111} \right)^2$$

Number of photon per electron per MeV produce by a 50 MeV - 20 mAmp electron beam on different converter material



Photon cone angle



- The photon cone from the interaction of the electron with the heavy nucleus is given by;

$$\langle \Theta^2 \rangle^{1/2} \approx 1/\gamma = m_e c^2 / E$$

- For $E = 50$ MeV, $\langle \Theta^2 \rangle^{1/2}$ is ~ 10 mRad and 100 mRad at 5 MeV.

Schematic Layout

- The electron beam impinges into the Hg converter and the resulting gamma beam interact with the ^{238}U target nuclei to produce photofission.
- The fission recoils stop in the target material.
- The atoms diffuse to the surface and effuse to the ion source to produce a Rare Isotope Beam. (Similar processes as for proton induced RIB)

electron
Beam

Gamma Beam

UC_x Target

Converter

Ion
Source


RIB

Photon Interaction

- There are three processes by which a photon can interact with matter. The relative importance depends on the photon energy.
- At low energy the photon < 0.1 MeV the photon will interact via the photoelectric effect. The cross section for this process falls very rapidly with photon energy,
- At photon energy up to 5 MeV the Compton scattering is the dominant process.
- At higher energy the photon converts into an electron-positron pair in the electrical field of a nucleus.
- The result of these processes is that the photon intensity is attenuated.

Gamma Attenuation



- Once the gamma rays are produced in the converter there is a probability that the gamma ray produces an electron-positron pair,
- It is the same when the gamma rays enter the target material.




e^+e^- pair production

$$\sigma_{e^+e^-} = \alpha Z^2 r_e^2 \left[\frac{28}{9} \ln(2k) - \frac{28}{9} f(Z) - \frac{218}{27} \right]$$

$$k = \frac{E_\gamma}{m_0 c^2}$$




Residual Photon distribution



- To estimate the number of fission induced by photon interaction with ^{238}U we have to integrate the residual photon spectrum with the GDR differential cross section.


Optimization

- **Specifications:**
 - **Electron initial energy:** 50 MeV,
 - **Electron beam intensity:** 10 mA,
 - **Converter material:** Hg,
 - **^{238}U thickness:** 15 g/cm²,
E. Jacobs *et al.*, Phys. Rev. C21 (1980) 237, used the same target thickness.
- **Optimum is 1,2 X^{Hg}₀.**




Optimization, electron energy

- Optimization of the electron energy, the following plot shows the number of induced fissions as a function of the primary electron beam energy.
- Calculation compared to measurements.





Yield Distribution





Yield distribution

- Yield of rare isotopes, using the fission yield distribution for 7×10^{13} f/s.



Yield distribution



- Yield of rare isotopes, using the fission yield distribution for 7×10^{13} f/s.



Fission Product Yields of ${}^{238}\text{U}$ Fission Decay,
T.R. England and B.F. Rider, LA-UR-94-3106,

Yield distribution

- Yield of rare isotopes, using the fission yield distribution for 7×10^{13} f/s.




Conclusion

- **New Target Stations design will allow us to exchange target much faster. The goal is to have a new target/ion source assembly ready within 2 days instead of ~ 4 weeks**
- **To accomplish this we will have the target/ion source into a true containment box.**
- **It will allow us to operate air sensitive target material, without having the risk spreading contamination during transport between target-station and hot-cell.**
- **eLINAC can provide clean neutron rich beams.**


Neutron Rich Beams

Neutron
rich
beams




These beams
are not produced
with photofission

Neutron Rich Beams



Conclusion

- eLINAC can provide clean neutron rich beams.
- eLINAC can produce photofission at a rate $\sim 10^{14}/\text{s}$, allowing a third RIB delivery simultaneously to ISAC users.
- eLINAC can provide ^8Li beam to β -NMR, $^9\text{Be}(\gamma, p)^8\text{Li}$.
- One of the new target station will allow RIB development, \Rightarrow new beams to ISAC users.



- **Thank you.**



- + 13 FTE, 6 Technicians, 5 Scientists, 2 Engineers.